

## COLLAPSIBLE CONTAINER

### FIELD OF THE INVENTION

5 The present invention relates to a collapsible container, and more particularly to a container that may be collapsed for easy storage when it is not in use and extended again for use at any time.

### 10 BACKGROUND OF THE INVENTION

Fig. 1 shows a conventional container structure that usually includes a rectangular container 30 and a corresponding cover cap 40. Both the container 30 and  
15 the cover cap 40 are typically made of metal material, plastics, cardboard, or other suitable materials either through integral molding or bending the material in a predetermined manner. However, either the integrally molded or the bent container 30 and cover  
20 cap 40 are not collapsible to a reduced volume. Conventional cartons are one example of this type of container structure, and could not be collapsed without tearing apart and thereby damaging joints of different parts of the cartons, making the collapsed cartons  
25 incomplete and ugly.

When the above conventional container structure consisting of a container 30 and a cover cap 40 is initially produced, a large space is required to store and transport it. And, when the container and the cover  
5 cap are not in use, they could not be conveniently collapsed for storage.

#### SUMMARY OF THE INVENTION

10 A primary object of the present invention is to provide a collapsible container, so that the container could be collapsed when it is not in use to facilitate easy storage and transport thereof, and extended again at any time for containing different articles as desired.

15

Another object of the present invention is to provide a collapsible cover cap for removably closing an open top of the above-mentioned collapsible container without increasing the volume of the container when  
20 it is collapsed for storage or transport.

To achieve the above and other objects, the collapsible container of the present invention includes a rectangular bottom, a front and a rear rectangular wall  
25 pivotally turnably connected to a front and a rear edge, respectively, of the bottom along two folding lines,

two rectangular side walls pivotally turnably connected to two lateral ends of each of the front and the rear wall along two folding lines, and two locating flaps pivotally turnably connected to two lateral edges of the bottom along two folding lines. Each of the two locating flaps is an isosceles triangle having two equal lateral sides separately corresponding to a diagonal of the side wall. Moreover, fastening means are correspondingly provided on an inner surface of each side wall and an outer surface of the locating flap to enable detachable connection of the side walls to the locating flaps and thereby permitting free collapse and extension of the container at any time.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The structure and the technical means adopted by the present invention to achieve the above and other objects can be best understood by referring to the following detailed description of the preferred embodiments and the accompanying drawings, wherein

Fig. 1 is a perspective view of a conventional container and a cover cap thereof;

Fig. 2 is a top perspective view of a container according

to a first embodiment of the present invention in a collapsed state;

Fig. 3 is a perspective view showing the manner of turning  
5 and folding different parts of the collapsed container of Fig. 1 to provide an extended container for use;

Fig. 4 is a perspective view of the container of the first embodiment of the present invention in a fully  
10 extended state for use;

Fig. 5 is a perspective view of a cover cap for the container of Fig. 4 in a collapsed state;

15 Fig. 6 is a perspective view showing the manner of turning and folding different parts of the collapsed cover cap of Fig. 5 to provide a cover cap for use;

Fig. 7 is a perspective view of the cover cap of the present invention in a fully extended state for use;  
20

Fig. 8 shows the use of the cover cap of Fig. 7 to cover an open top of the container of Fig. 4;

25 Fig. 9 is a top perspective view of a container according to a second embodiment of the present invention in a

collapsed state;

Fig. 10 is a perspective view showing the manner of turning and folding different parts of the collapsed container of Fig. 9 to provide an extended container for use;

Fig. 11 is a perspective view of the container of the second embodiment of the present invention in a fully extended state for use; and

Fig. 12 shows one type of fastening means used in the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention relates to a collapsible container 1 and a collapsible cover cap 2 for the container 1.

Please refer to Figs. 2 to 4 in which a collapsible container 1 according to a first embodiment of the present invention is shown. As shown, the container 1 mainly includes a rectangular bottom 11, a front and a rear rectangular wall 12, 13 pivotally turnably connected to a front and a rear edge, respectively,

of the bottom 11 along two folding lines 10, two rectangular side walls 14 pivotally turnably connected to two lateral ends of each of the front and the rear wall 12, 13 along two folding lines 10, and two locating  
5 flaps 15 pivotally turnably connected to two lateral edges of the bottom 11 along two folding lines 10. Each of the side walls 14 has a width, that is, a length of the side wall extended from the lateral end of the front or the rear wall, that does not exceed one half  
10 of an overall length of each lateral edge of the bottom between the front and the rear edge. Each of the two locating flaps 15 is an isosceles triangle having two equal lateral sides 151 separately corresponding to a diagonal of the side wall 14. Moreover, two  
15 detachably connectable mating fastening elements forming a fastening means 3 are correspondingly provided on an inner surface of each side wall 14 and an outer surface of the locating flap 15.

20 Please refer to Figs. 5 to 7 in which a collapsible cover cap 2 according to the present invention is shown. As shown, the cover cap 2 mainly includes a rectangular top 21, a front and a rear skirt 22, 23 pivotally turnably connected to a front and a rear edge, respectively,  
25 of the top 21 along two folding lines 20, a side skirt 24 pivotally turnably connected to each lateral edge

of the top 21 along a folding line 20, and two triangular connecting pieces 25 pivotally turnably connected two lateral ends of each of the skirts 22, 23, 24. Any two of the triangular connecting pieces 25 that are located  
5 between two adjacent skirts 22, 24 or 23, 24 are integrally connected to and foldable toward each other along a folding line 20. Moreover, two mating fastening elements that together form a fastening means 3 are provided on any two adjacent triangular connecting  
10 pieces 25 at their outer surfaces that would face toward each other after the two adjacent triangular connecting pieces 25 are folded along the folding line 20 to extend into the cover cap 2.

15 Fig. 8 shows the container 1 and the cover cap 2 of the present invention in a fully extended state for use.

In the case the container 1 and the cover cap 2 are  
20 integrally formed from a cardboard, the folding lines 10, 20 may be formed by means of pre-folding the cardboard at predetermined positions. Or, in the case the container 1 and the cover cap 2 are integrally formed from a plastic board, the folding lines 10, 20 may be  
25 formed by means of integrally forming thinner portions on the plastic board at predetermined positions.

Alternatively, the container 1 and the cover cap 2 may be made of a sheet metal, a plastic board, or a cardboard to include separated parts, including the bottom 11 and the walls 12, 13, 14, and the top 21 and the skirts 22, 23, 24, and cloth or non-woven fabric is attached to inner or outer surfaces of these separated parts to connect them together and form the complete container 1 and cover cap 2. In the latter case, the cloth or the non-woven fabric provides bendable folding lines 10, 20 at joints of any two adjacent parts.

When the container 1 having the above-described structure is initially produced and has not been used to hold anything, it may be collapsed by means of pivotally turning the front and the rear wall 12, 13 toward an upper side of the bottom 11, as shown in Fig. 2. At this point, the side walls 14 and the locating flaps 15 are automatically brought to a lying position, so that the whole container 1 is in a completely flat state to largely reduce the space needed to store, transport, or display the container 1. And, when it is desired to use the container 1, a user needs only to turn the front and the rear wall 12, 13 from the flat position into an upright position, so that the side walls 14 and the locating flaps 15 are automatically brought to the upright position at the same time, as



shown in Fig. 3. Thereafter, use the fastening means 3 to hold the two side walls 14 and the one locating flap 15 at the same lateral side of the container 1 in a firmly connected state, as shown in Fig. 4. Then, 5 the container 1 is ready for use. And, when the container 1 is not in use, the fastening means 3 on the side walls 14 and the locating flaps 15 may be detached for the container 1 to be collapsed into the fully flat state again by turning the front and the 10 rear walls 12, 13 to the upper side of the bottom 11.

Similarly, when the cover cap 2 having the above-described structure is initially produced and has not been used to cover the container 1, it may be 15 collapsed by means of pivotally turning the front and the rear skirt 22, 23 toward a lower side of the top 11, and pivotally turning the two lateral skirts 24 outward to a lying position, as shown in Fig. 5, so that the cover cap 2 is in a flat state to occupy a 20 largely reduced space. When it is desired to use the cover cap 2, a user needs only to turn the front, the rear, and the lateral skirts 22, 23, 24 to an upright position, fold and orient the two adjacent triangular connecting pieces 25 at each lateral end of the skirts 25 22, 23, 24 toward the top 21, as shown in Fig. 6, and use the fastening means 3 to hold the folded adjacent

connecting pieces 25 in a fitly contacted position,  
as shown in Fig. 7. Then, the cover cap 2 is ready for  
use.

5 The fastening means 3 including two mating fastening  
elements may be a snap including a ball side 31 and  
a socket side 32 that are separately and correspondingly  
fixed to an inner surface of the side wall 14 and an  
outer surface of the locating flap 15 on the container  
10 1, and outer surfaces of any two adjacent connecting  
pieces 25 on the cover cap 2, as shown in Figs. 3 and  
5, so as to hold the container 1 and cover cap 2 in  
the extended state for use. Alternatively, the  
fastening means 3 may be a magic tape (that is, Velcro  
15 tape) consisting of a hook tape 33 and a loop tape 34,  
as shown in Fig. 12. Similarly, the hook tape 33 and  
the loop tape 34 are separately and correspondingly  
fixed to an inner surface of the side wall 14 and an  
outer surface of the locating flap 15 on the container  
20 1, and outer surfaces of any two adjacent connecting  
pieces 25 on the cover cap 2, so as to hold the container  
1 and cover cap 2 in the extended state for use.

Figs. 9 to 11 illustrates a collapsible container 1  
25 according to a second embodiment of the present  
invention. In the second embodiment, the container 1

includes a rear wall 13' higher than a front wall 12,  
so that two side walls 14' pivotally turnably connected  
to two lateral edges of the rear wall 13' along two  
folding lines 10 are two specific trapezoids. Each of  
5 the two isosceles triangles of the locating flaps 15  
in the second embodiment is connected at one of its  
two equal lateral sides 151 to an inner surface of the  
trapezoidal side wall 14'. The container 1 of the  
second embodiment may be used as a document, book, or  
10 magazine folder and is also collapsible to occupy a  
reduced space, as shown in Fig. 9, and extendable for  
convenient use, as shown in Fig. 11.

As can be seen from Figs. 3, 10, and 12, the front wall  
15 12 of the container 1 is provided with a strip-shaped  
grip 16 having two ends connected to the front wall  
12, enabling the container 1 to be more conveniently  
handled.